

The high end: Card Attachment Secure System - CASS C8000

Quick, individual and flexible card processing

Those who wish to process plastic cards in the most flexible way and who do not wish to compromise, need an individually configured CASS C8000. With its high working speed of up to 8000 cycles per hour, our most powerful system becomes either a specialist or a multi-talent. It is entirely up to the customer what he wants. And there is always the possibility to have the system extended at a later stage. The range of employment of the CASS C8000 mainly lies in areas

where extremely high requirements are necessary: because enormous amounts of mail have to be processed around the clock. Or because a large number of small lot sizes have to be processed. But there are more reasons for the employment of the CASS C8000. One of them is its amazing versatility which, if required, allows for the operation of the system without the card channel as a single- or multiple channel insertion system.

Another reason is the simplicity with which the CASS C8000 can be controlled by means of the Windows –based DIALok operating interface and with which the process data can be fed in. For all these reasons, but also for some other good reasons, the list of companies and organisations which process their mail with our CASS C8000, seems to be already something like the "Who is who" of the card branch.



Important performance features:

- Modular structure
- Up to 8000 cards per hour
- MS-Windows® operating system
- 1-2 cards per form are standard, 3-4 cards as an option
- Variable card positioning and -fixing
- 5mm tolerance for edges and fold
- Affixing tape with 38mm (1.5") width and a length of 8-15mm (0.3" to 0.6")

Reading options for carriers:

- Barcode/OMR/OCR-alignment for forms printed off-line
- Barcodes 39, 2/5, 128 and others
- OCR by camera / software
- In-line or off-line printing respectively by card reading or database
- Continuous or single sheet printing
- Upgradable for future demands

Reading options for plastic cards:

- Magnetic stripe, chip-reading, OCR, Barcodes 39, 2/5, 128 and others

Many configuration options, such as:

- Personalized 2. and 3. pages
- Multiple folds
- Personalized MICR check insertion
- Card thickness 0,32 - 0,9mm



Otto Künnecke

Ideas create solutions

Otto Künnecke GmbH

Bülte 1 • 37603 Holzminden • Germany

Tel +49 (0) 5531 9300 – 0 • Fax +49 (0) 5531 9300 – 903 • contact@kuennecke.com • www.kuennecke.com