

CS70 Cloud Speaker Payment Terminal

QR Code Reader + EMV Contactless





www.paxtechnology.com



SPECIFICATIONS	CS70 DQR
o Operating System	Monitor
Processor	32 bit ARM CPU
D Memory	8MB RAM + 20MB Flash
Card Readers	EMV Contactless ISO14443 Type A & Type B Mifare®
Display	2.4 inch 128 x 64 Pixels Black & White Screen
匚] QR Display	3.5 inch 320 x 480 Pixels Color Screen
((၅)) Connectivity	4G CAT 1 + WiFi
Battery	2600mAh 3.7V
՝ LED Indicators	4 RF Indicators 1 Power Indicator
SIM / SAM	1 Nano SIM
෯ Keys / Buttons	19 Keys: Power ON/0FF 0~9 Back Clear Entry V \uparrow V \downarrow Function Menu Card Pay
[_] Physical	125 x 95 x 150mm, 323g (Including Battery)
幻 》 Audio	4Ω , 3W 1 Speaker
Derts	1 Туре-С
🌀 Environmental	-10°C ~ 50°C (14°F ~ 122°F) Operating Temperature -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature -5%-96% Relative Humidity, Non-Condensing
Certifications	PCI PTS 6.x SRED EMV CL L1 MCL VCPS Expresspay RuPay TQM BIS WPC RoHS







This document is provided to you for informational purposes only. All features and specifications are subject to change without notice. PAX and the PAX logo are either trademarks or registered trademarks of PAX Technology Limited in China and/or other countries. The Bluetooth word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by PAX Technology Limited is under license. Other trademarks and trade names are those of their respective owners. © 2024 PAX Technology Limited. All rights reserved.

